TM TECHNOLOGIE

ITECH M5 105 M ST W
TM-IT.M5STM160W

Click on the selected icon to download the file:

No: 0926

No: 4570/2022
Valid until:
10.04.2027

No: 88-137960


No:
B_BK_60112_0422_2024
Valid until:
24.01.2030

No: 0926


No: 0926

No: DIT.V1.01


No: V3.0



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**ITECH**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**standard**
Operating mode	**M**
Duration time	**1 h**
Protection degree	**IP65**
Impact protection degree	**IK06**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, ceiling, at an angle**
Luminous flux emergency	**524 lm**
Light source	**LED**
Maximum light power	**4.5 W**
Active power	**6 W**
LED lifetime	**100000 h**
Nominal voltage AC	**210-250 V**
Colour temperature	**5700 K**
Minimum temperature	**+ 0 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**24 months**
Net dimensions **H x Ø** [±2 mm]	**74 mm x 171 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	4	12	4	12
3	4	13,5	4	13,5
4	4,5	15,5	4,5	15,5
5	5	17	5	17
6	5,5	18,5	5,5	18,5
7	6	19,5	6	19,5
8	6	20,5	6	20,5
9	6,5	21,5	6,5	21,5
10	6	22,5	6	22,5

Emin ≥ 0,5 lx