

ITECH M5 105 M ST W TM-IT.M5STM160W

Click on the selected icon to download the file:



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960



No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925




No: 0925




No: DIT_001






No: V2.12



Producer	TM Technologie
Application	anti-panic lighting
Family	ITECH
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	M
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	524 lm
Light source	LED
Maximum light power	4.5 W
Active power	6 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
Warranty (body, electronics, light source)	24 months
Net dimensions H x Ø [±2 mm]	74 mm x 171 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	4	12	4	12
3	4	13,5	4	13,5
4	4,5	15,5	4,5	15,5
5	5	17	5	17
6	5,5	18,5	5,5	18,5
7	6	19,5	6	19,5
8	6	20,5	6	20,5
9	6,5	21,5	6,5	21,5
10	6	22,5	6	22,5

$E_{min} \geq 0,5 \text{ lx}$