

# ONTEC C M1 180 NM ST W TM-OC.M1STN800W

Click on the selected icon to download the file:



No: 0125



No: 4397/2021  
Valid until:  
11.09.2026



No: 88-128463  
Valid until:  
25.05.2026



No:  
B\_BK\_60112\_0424\_2024  
Valid until:  
24.01.2030



No: 0125



No: 2291559.02-  
UAE  
Valid until:  
05.11.2026



No: 0125



No: DIT\_001



No: V1.14



|  |                                      |
|--|--------------------------------------|
| Producer                                   | <b>TM Technologie</b>                |
| Application                                | <b>anti-panic lighting</b>           |
| Family                                     | <b>ONTEC C</b>                       |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>               |
| Version                                    | <b>standard</b>                      |
| Operating mode                             | <b>NM</b>                            |
| Duration time                              | <b>3 h</b>                           |
| Protection degree                          | <b>IP20</b>                          |
| Impact protection degree                   | <b>IK03</b>                          |
| Appliance classes                          | <b>II</b>                            |
| Material                                   | <b>plastic</b>                       |
| Installation method*                       | <b>flush-mounted, ceiling</b>        |
| Luminous flux emergency                    | <b>167 lm</b>                        |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>3 W</b>                           |
| Active power                               | <b>1.2 W</b>                         |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| LED lifetime                               | <b>50000 h</b>                       |
| Colour temperature                         | <b>5700 K</b>                        |
| Minimum temperature                        | <b>+10 °C</b>                        |
| Maximum temperature                        | <b>+35 °C</b>                        |
| Battery                                    | <b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b> |
| Warranty (body, electronics, light source) | <b>24 months</b>                     |
| Net dimensions <b>H x Ø</b> [±2 mm]        | <b>14 mm x 90 mm</b>                 |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



|     |     |      |     |      |
|-----|-----|------|-----|------|
| 2,5 | 3   | 7,5  | 3   | 7,5  |
| 3   | 3,5 | 8,5  | 3,5 | 8,5  |
| 4   | 4   | 10   | 4   | 10   |
| 5   | 4,5 | 11,5 | 4,5 | 11,5 |
| 6   | 4   | 13   | 4   | 13   |
| 7   | 3,5 | 14   | 3,5 | 14   |
| 8   | 2,5 | 15   | 2,5 | 15   |
| 9   | 2,5 | 15   | 2,5 | 15   |
| 10  | 2   | 15   | 2   | 15   |

$E_{min} \geq 0,5 \text{ lx}$