

# ONTEC S M1 180 M ST W TM-OS.M1STM860W

Click on the selected icon to download the file:



No: 1025



No: 4662/2022  
Valid until:  
02.06.2027



No: 88-139797



No:  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1025



No: 2291559.02-  
UAE  
Valid until:  
05.11.2026



No: 1025




No: V1





No: V3.0



Producer	<b>TM TECHNOLOGIE</b>
Application	<b>anti-panic lighting</b>
Family	<b>ONTEC S</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>standard</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b>
Luminous flux emergency	<b>150 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
Active power	<b>3.3 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+ 0 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>24 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>272 mm x 40 mm x 144 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3	8,5	3	8,5
3	3,5	9	3,5	9
4	3,5	10,5	3,5	10,5
5	3,5	11,5	3,5	11,5
6	3	12,5	3	12,5
7	3	13	3	13
8	3	13,5	3	13,5
9	2	14	2	14
10	3	13	3	13

$E_{min} \geq 0,5 \text{ lx}$