

# PRIMO A C1 180 NM AT B TM-A0.C1.AT04B



No: 1725



No: 4329/2021  
Valid until:  
19.05.2026



No: B\_BK\_60112\_0427\_2024  
Valid until:  
24.01.2030



No: 1725



No: DC-UAE-0180  
Valid until:  
19.05.2026



No: 1725





No: DIT\_001



No: V1.2



Producer	<b>TM Technologie</b>
Application	<b>escape route lighting</b>
Family	<b>PRIMO A</b>
Colour/Colour - RAL	<b>black , RAL9005</b>
Version	<b>autotest</b>
Operating mode	<b>NM</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK03</b>
Appliance classes	<b>I</b>
Material	<b>steel</b>
Installation method*	<b>surface, ceiling</b>
Luminous flux emergency	<b>444* lm</b>
Light source	<b>LED</b>
Maximum light power	<b>4.5 W</b>
Active power	<b>4.1 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+5 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 6.4V 3.0-3.2Ah</b>
Warranty (body, electronics, light source)	<b>36 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>273 mm x 61 mm x 75 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.