

PRIMO APZ 30D CB W TM-AZ.30D.CB01W



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No: B_BK_60112_0427_2024
Valid until:
24.01.2030



No: 1725



No: DC-UAE-0180
Valid until:
19.05.2026




No: 1725



No: V1.1



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	PRIMO APZ
Colour/Colour - RAL	white , RAL9003
Colour structure	painted
Version	CB - central battery
Operating mode	CB
Protection degree	IP20
Impact protection degree	IK07
Appliance classes	I
Material	steel
Installation method*	ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	319x193 mm
Evacuation sign dimensions	300x150 mm
Pictogram type	foil
Graphic number	K3, D3
Luminous flux	>500 cd/m²
Visibility	30 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
Light source	LED
Maximum light power	1.8 W
LED lifetime	50000 h
Minimum temperature	-15 °C
Maximum temperature	+55 °C
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	324 mm x 61 mm x 698 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.