TM TECHNOLOGIE

INDUST B2L CBM H
TM-B2.0LCBM09LH

Click on the selected icon to download the file:

CE No: 3626

CNBOP-PIB No: 5386/2024
Valid until: 15.05.2029

UKCA No: 3626

REACH compliant


RoHS compliant No: 3626

LED No: DIT.V2.03

No: V1.0



Producer	**TM TECHNOLOGIE**
Application	**evacuation route direction, tunnel lighting**
Family	**INDUST B2**
Colour	**titanium-stabilised stainless steel**
Version	**CBM - Central addressable modulation battery**
Operating mode	**CB**
Protection degree	**IP66, IP69**
Impact protection degree	**IK08**
Appliance classes	**I**
Material	**stainless steel**
Installation method*	**surface, wall**
Luminous flux	**>200 cd/m²**
Luminous flux emergency	**1000 lm**
Light source	**LED**
Maximum light power	**5 W**
Active power	**13.5 W**
LED lifetime	**50000 h**
Nominal voltage AC	**220-240 V**
Nominal voltage DC	**186-254 V**
Colour temperature	**5700 K**
Minimum temperature	**-25 °C**
Maximum temperature	**+45 °C**
Battery	**-**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**481 mm x 75 mm x 692 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.