

# INDUST B 20L CB DALI-2 H TM-B2.0LCD0090H

Click on the selected icon to download the file:



No: 3625



No: 5386/2024  
Valid until:  
15.05.2029



No: 3625



No: 2016



No: 3625



No: V1.0



Producer	<b>TM TECHNOLOGIE</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction, tunnel lighting</b>
Family	<b>INDUST B2</b>
Version	<b>CD - CB DALI2</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP66, IP69</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>I</b>
Material	<b>stainless steel</b>
Colour structure	<b>raw</b>
Installation method*	<b>surface, wall</b>
Adapted to use a pictogram	<b>yes</b>
Luminous flux	<b>&gt;200 cd/m<sup>2</sup></b>
Luminous flux emergency	<b>1000 lm</b>
Nominal voltage AC	<b>220-240 V</b>
Nominal voltage DC	<b>186-254 V</b>
Light source	<b>LED</b>
Maximum light power	<b>5 W</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-25 °C</b>
Maximum temperature	<b>+45 °C</b>
Battery	<b>-</b>
DALI type	<b>A</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>481 mm x 75 mm x 692 mm</b>

