

INDUST B 3DF CB DALI-2 H TM-B3.DFCD0090H

Click on the selected icon to download the file:



No: 3725



No: 5436/2024
Valid until:
09.07.2029



No: 3725



No: 2016




No: 3725



No: V1.0



| | |
|--|--|
| Producer | TM Technologie |
| Application | evacuation route direction, tunnel lighting |
| Family | INDUST B3 |
| Version | CD - CB DALI2 |
| Operating mode | CB |
| Protection degree | IP66, IP69 |
| Impact protection degree | IK08 |
| Appliance classes | I |
| Material | stainless steel |
| Installation method* | surface, wall |
| Luminous flux | >200 cd/m² |
| Light source | LED |
| Maximum light power | 1.5 W |
| Active power | * W |
| Nominal voltage AC | 220-240 V |
| Nominal voltage DC | 186-254 V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | -25 °C |
| Maximum temperature | +45 °C |
| Battery | - |
| DALI type | A |
| Warranty (body, electronics, light source) | 60 months |
| Net dimensions L x W x H [±2 mm] | 560 mm x 105 mm x 435 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.