
# INDUST B4D CBM H
# TM-B4.D0CBM090H

Click on the selected icon to download the file:

No: 3726 | No: 5436/2024 Valid until: 09.07.2029 | No: 3726 | No: 3726 | No: DIT.V2.03 | No: V1.0




| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Application | **evacuation route direction, tunnel lighting** |
| Family | **INDUST B4** |
| Colour | **titanium-stabilised stainless steel** |
| Version | **CBM - Central addressable modulation battery** |
| Operating mode | **CB** |
| Protection degree | **IP66, IP69** |
| Impact protection degree | **IK08** |
| Appliance classes | **I** |
| Material | **stainless steel** |
| Installation method* | **surface, wall** |
| Luminous flux | **>200 cd/m²** |
| Light source | **LED** |
| Maximum light power | **1.6 W** |
| Active power | **7.1 W** |
| LED lifetime | **50000 h** |
| Nominal voltage AC | **220-240 V** |
| Nominal voltage DC | **186-254 V** |
| Colour temperature | **5700 K** |
| Minimum temperature | **-25 °C** |
| Maximum temperature | **+45 °C** |
| Battery | **-** |
| Warranty (body, electronics, light source) | **60 months** |
| Net dimensions **L x W x H** [±2 mm] | **560 mm x 105 mm x 635 mm** |




* Some of mounting methods are possible only with additonal accessory dedicated for that product.