TM TECHNOLOGIE


BOA IN RC1 CBM
TM-BIRC1CBM0000


Click on the selected icon to download the file:

No: 1126 | No: 5912/2025 Valid until: 29.11.2030 | No: B_BK_60112_0421_2024 Valid until: 24.01.2030 | No: 1126 | No: 1126 | No: DIT.V2.03 | No: V2.1



Producer	**TM TECHNOLOGIE**
Application	**escape route lighting**
Family	**BOA IN**
Version	**CBM - Central addressable modulation battery**
Operating mode	**CB**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**II**
Material	**plastic**
Installation method*	**ceiling, flush-mounted, surface**
Luminous flux emergency	**293 lm**
Light source	**LED**
Maximum light power	**2.5 W**
Active power	**4.3 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**186-254 V**
Colour temperature	**5700 K**
Minimum temperature	**-15 °C**
Maximum temperature	**+55 °C**
Battery	**-**
Power Factor Correction	**0,83**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **H x Ø** [±2 mm]	**21 mm x 50 mm**





* Some of mounting methods are possible only with additonal accessory dedicated for that product.