

# BOA IN RC1 CBM TM-BIRC1CBM0000

Click on the selected icon to download the file:



No: 1125



No: 5912/2025  
Valid until:  
29.11.2030



No: B\_BK\_60112\_0421\_2024  
Valid until:  
24.01.2030



No: 1125



No: 1125





No: V2



No: V2.1



Producer	<b>TM TECHNOLOGIE</b>
Application	<b>escape route lighting</b>
Family	<b>BOA IN</b>
Version	<b>CBM - Central addressable modulation battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK03</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>ceiling, flush-mounted, surface</b>
Luminous flux emergency	<b>293 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
Active power	<b>4.3 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+55 °C</b>
Battery	<b>-</b>
Power Factor Correction	<b>0,83</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>H x Ø</b> [±2 mm]	<b>21 mm x 50 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.