

# BOA IN RM1 180 NM DATA2 TM-BIRM1DDN8000

Click on the selected icon to download the file:



No: 1125



No: 5912/2025  
Valid until:  
29.11.2030




No:  
B\_BK\_60112\_0421\_2024  
Valid until:  
24.01.2030



No: 1125



No: 1125





No: V1



No: V2.1



Producer	<b>TM TECHNOLOGIE</b>
Application	<b>anti-panic lighting</b>
Family	<b>BOA IN</b>
Version	<b>DATA2</b>
Operating mode	<b>NM</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK03</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>ceiling, flush-mounted, surface</b>
Luminous flux emergency	<b>150 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2.5 W</b>
Active power	<b>1.2 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+10 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>H x Ø</b> [±2 mm]	<b>21 mm x 50 mm</b>



h	a	b	c	d
2,5	3	8,5	3	8,5
3	3	9,5	3	9,5
4	3,5	11	3,5	11
5	3	12	3	12
6	3	13	3	13
7	3	13	3	13
8	3,5	13	3,5	13
9	3	13	3	13
10	2,5	13,5	2,5	13,5

E<sub>min</sub> ≥ 0,5 lx

\* Some of mounting methods are possible only with additional accessory dedicated for that product.