

BOA IN RM1 180 NM ST TM-BIRM1STN8000

Click on the selected icon to download the file:



No: 1125



No: 5912/2025
Valid until:
29.11.2030



No: B_BK_60112_0421_2024
Valid until:
24.01.2030



No: 1125



No: 1125





No: DIT_001



No: V2.1



Producer	TM Technologie
Application	anti-panic lighting
Family	BOA IN
Version	standard
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Installation method*	ceiling, flush-mounted, surface
Luminous flux emergency	150 lm
Light source	LED
Maximum light power	2.5 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	24 months
Net dimensions H x Ø [±2 mm]	21 mm x 50 mm



h	a	b	c	d
2,5	3	8,5	3	8,5
3	3	9,5	3	9,5
4	3,5	11	3,5	11
5	3	12	3	12
6	3	13	3	13
7	3	13	3	13
8	3,5	13	3,5	13
9	3	13	3	13
10	2,5	13,5	2,5	13,5

Emin ≥ 0,5 lx

* Some of mounting methods are possible only with additional accessory dedicated for that product.