
BOA IN RM1 180 NM ST
TM-BIRM1STN8000


Click on the selected icon to download the file:

No: 1126 | No: 5912/2025 Valid until: 29.11.2030 | No: B_BK_60112_0421_2024 Valid until: 24.01.2030 | No: 1126 | No: 1126 | No: DIT.V1.01 | No: V2.1



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**BOA IN**
Version	**standard**
Operating mode	**NM**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**II**
Material	**plastic**
Installation method*	**ceiling, flush-mounted, surface**
Luminous flux emergency	**150 lm**
Light source	**LED**
Maximum light power	**2.5 W**
Active power	**1.2 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**24 months**
Net dimensions **H x Ø** [±2 mm]	**21 mm x 50 mm**





h	a	b	c	d
2,5	3	8,5	3	8,5
3	3	9,5	3	9,5
4	3,5	11	3,5	11
5	3	12	3	12
6	3	13	3	13
7	3	13	3	13
8	3,5	13	3,5	13
9	3	13	3	13
10	2,5	13,5	2,5	13,5

Emin ≥ 0,5 lx

* Some of mounting methods are possible only with additonal accessory dedicated for that product.