
INDUST L 1D CB DALI 2 N
TM-IL.L1CD0090N

Click on the selected icon to download the file:

No: 2726 | No: 4741/2022 Valid until: 12.09.2027 | No: 2726 | No: 7505 | No: 2726 | No: V1.0



Producer	**TM TECHNOLOGIE**
Application	**tunnel lighting , evacuation route direction**
Family	**INDUST L**
Colour	**raw**
Version	**CD - CB DALI2**
Operating mode	**CB**
Protection degree	**IP66, IP69**
Impact protection degree	**IK08**
Appliance classes	**I**
Material	**stainless steel**
Installation method*	**surface, wall**
Luminous flux emergency	**1350 lm**
Light source	**LED**
Maximum light power	**40.7 W**
Active power	**42.2 W**
LED lifetime	**50000 h**
Nominal voltage AC	**220-240 V**
Nominal voltage DC	**186-254 V**
Colour temperature	**525 nm**
Minimum temperature	**-25 °C**
Maximum temperature	**+45 °C**
Battery	**-**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**1460 mm x 39 mm x 1910 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.