

INDUST N M1 60 NM AT N TM-IN.M1ATN690N

Click on the selected icon to download the file:



No: 2825



No: 5048/2023
Valid until:
27.07.2028



No: 2825



No: 2825




No: DIT_001



No: V1.3



| | |
|--|--------------------------------------|
| Producer | TM Technologie |
| Application | anti-panic lighting |
| Family | INDUST N |
| Version | autotest |
| Operating mode | NM |
| Duration time | 1 h |
| Protection degree | IP66, IP69 |
| Impact protection degree | IK08 |
| Appliance classes | I |
| Material | stainless steel |
| Installation method* | surface, wall |
| Luminous flux emergency | 327 lm |
| Light source | LED |
| Maximum light power | 3 W |
| Active power | 1.2 W |
| Nominal voltage AC | 210-250 V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | + 0 °C |
| Maximum temperature | +40 °C |
| Battery | LiFePO4/C (LN) 3.2V 1.5-1.6Ah |
| Warranty (body, electronics, light source) | 36 months |
| Net dimensions L x W x H [±2 mm] | 243 mm x 114 mm x 195 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.