

# INDUST N M1 CB N TM-IN.M1CB0090N

Click on the selected icon to download the file:



No: 2825



No: 5048/2023  
Valid until:  
27.07.2028



No: 2825





No: 2825



No: V1.3



Producer	<b>TM Technologie</b>
Application	<b>anti-panic lighting</b>
Family	<b>INDUST N</b>
Version	<b>CB - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP66, IP69</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>I</b>
Material	<b>stainless steel</b>
Installation method*	<b>surface, wall</b>
Luminous flux emergency	<b>327 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>3 W</b>
Active power	<b>4.5 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+55 °C</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [ $\pm 2$ mm]	<b>243 mm x 114 mm x 195 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.