
INDUST N M1 CBM B
TM-IN.M1CBM090B


Click on the selected icon to download the file:

No: 2826 | No: 5048/2023 Valid until: 27.07.2028 | No: 2826 | No: DIT.V2.03 | No: V1.3



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**INDUST N**
Colour	**black**
Colour - RAL	**RAL9005**
Version	**CBM - Central addressable modulation battery**
Operating mode	**CB**
Protection degree	**IP66, IP69**
Impact protection degree	**IK08**
Appliance classes	**I**
Material	**steel**
Installation method*	**surface, wall**
Luminous flux emergency	**327 lm**
Light source	**LED**
Maximum light power	**3 W**
Active power	**4.4 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**186-254 V**
Colour temperature	**5700 K**
Minimum temperature	**-15 °C**
Maximum temperature	**+55 °C**
Battery	**-**
Power Factor Correction	**0,83**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**243 mm x 114 mm x 195 mm**





* Some of mounting methods are possible only with additonal accessory dedicated for that product.