

# INDUST N M1 CBM W TM-IN.M1CBM090W

Click on the selected icon to download the file:



No: 2825



No: 5048/2023  
Valid until:  
27.07.2028



No: 2825



No: 2825





No: V2



No: V1.3



|  |   |
|--|---|
| Producer                                   | <b>TM TECHNOLOGIE</b>                               |
| Application                                | <b>anti-panic lighting</b>                          |
| Family                                     | <b>INDUST N</b>                                     |
| Colour/Colour - RAL                        | <b>white , RAL9003</b>                              |
| Version                                    | <b>CBM - Central addressable modulation battery</b> |
| Operating mode                             | <b>CB</b>   |
| Protection degree                          | <b>IP66, IP69</b>                                   |
| Impact protection degree                   | <b>IK08</b>   |
| Appliance classes                          | <b>I</b>  |
| Material                                   | <b>steel</b>  |
| Installation method*                       | <b>surface, wall</b>                                |
| Luminous flux emergency                    | <b>327 lm</b>                                       |
| Light source                               | <b>LED</b>  |
| Maximum light power                        | <b>3 W</b>  |
| Active power                               | <b>4.4 W</b>  |
| Nominal voltage AC                         | <b>210-250 V</b>                                    |
| Nominal voltage DC                         | <b>186-254 V</b>                                    |
| LED lifetime                               | <b>50000 h</b>                                      |
| Colour temperature                         | <b>5700 K</b>                                       |
| Minimum temperature                        | <b>-15 °C</b>                                       |
| Maximum temperature                        | <b>+55 °C</b>                                       |
| Battery                                    | <b>-</b>  |
| Warranty (body, electronics, light source) | <b>60 months</b>                                    |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>243 mm x 114 mm x 195 mm</b>                     |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.