

# INDUST N M1 60 NM ST N TM-IN.M1STN690N

Click on the selected icon to download the file:



No: 2825



No: 5048/2023  
Valid until:  
27.07.2028



No: 2825



No: 2825





No: V1



No: V1.3



|                                            |                                      |
|--------------------------------------------|--------------------------------------|
| Producer                                   | <b>TM TECHNOLOGIE</b>                |
| Application                                | <b>anti-panic lighting</b>           |
| Family                                     | <b>INDUST N</b>                      |
| Version                                    | <b>standard</b>                      |
| Operating mode                             | <b>NM</b>                            |
| Duration time                              | <b>1 h</b>                           |
| Protection degree                          | <b>IP66, IP69</b>                    |
| Impact protection degree                   | <b>IK08</b>                          |
| Appliance classes                          | <b>I</b>                             |
| Material                                   | <b>stainless steel</b>               |
| Installation method*                       | <b>surface, wall</b>                 |
| Luminous flux emergency                    | <b>327 lm</b>                        |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>3 W</b>                           |
| Active power                               | <b>1.2 W</b>                         |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| LED lifetime                               | <b>50000 h</b>                       |
| Colour temperature                         | <b>5700 K</b>                        |
| Minimum temperature                        | <b>+ 0 °C</b>                        |
| Maximum temperature                        | <b>+40 °C</b>                        |
| Battery                                    | <b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b> |
| Warranty (body, electronics, light source) | <b>24 months</b>                     |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>243 mm x 114 mm x 195 mm</b>      |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.