

ITECH C1 302 M AT W COLD TM-IT.C1ATM36CW



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960



No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 0925




No: DIT_001





No: V2.12



Producer	TM Technologie
Application	escape route lighting
Family	ITECH
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	238 lm
Light source	LED
Maximum light power	2 W
Active power	6.4 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-15 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C 6.4V 3.0Ah
Warranty (body, electronics, light source)	36 months
Net dimensions H x Ø [±2 mm]	74 mm x 171 mm





2,5	8	18,5	-	-
3	9,5	21	-	-
4	10,5	25	-	-
5	7	27	-	-
6	4,5	25	-	-
7	4,5	20	-	-
8	4,5	16	-	-
9	-	-	-	-
10	-	-	-	-

$E_{min} \geq 1 \text{ lx}$