

# ITECH C1 302 M AT W COLD TM-IT.C1ATM36CW

Click on the selected icon to download the file:



No: 0925



No: 4570/2022  
Valid until:  
10.04.2027



No: 88-137960



No:  
B\_BK\_60112\_0422\_2024  
Valid until:  
24.01.2030



No: 0925



No: 0925




No: DIT\_001



No: V2.12



Producer	<b>TM Technologie</b>
Application	<b>escape route lighting</b>
Family	<b>ITECH</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>autotest</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK06</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, ceiling, at an angle</b>
Luminous flux emergency	<b>238 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2 W</b>
Active power	<b>6.4 W</b>
Nominal voltage AC	<b>210-250 V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C 6.4V 3.0Ah</b>
Warranty (body, electronics, light source)	<b>36 months</b>
Net dimensions <b>H x Ø</b> [±2 mm]	<b>74 mm x 171 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	8	18,5	-	-
3	9,5	21	-	-
4	10,5	25	-	-
5	7	27	-	-
6	4,5	25	-	-
7	4,5	20	-	-
8	4,5	16	-	-
9	-	-	-	-
10	-	-	-	-

$E_{min} \geq 1 \text{ lx}$