

# ITECH C2 305 M DATA2 B

## TM-IT.C2DDM360B

Click on the selected icon to download the file:



No: 0925



No: 4570/2022  
Valid until:  
10.04.2027



No: 88-137960



No:  
B\_BK\_60112\_0422\_2024  
Valid until:  
24.01.2030



No: 0925



No: 0925




No: V1



No: V2.12



Producer	<b>TM Technologie</b>
Application	<b>escape route lighting</b>
Family	<b>ITECH</b>
Colour/Colour - RAL	<b>black , RAL9005</b>
Version	<b>DATA2</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK06</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, suspended, ceiling, at an angle</b>
Luminous flux emergency	<b>478 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>4.5 W</b>
Active power	<b>6 W</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>- V</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>+ 0 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C (LN) 6.4V 3.0-3.2Ah</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>H x Ø</b> [±2 mm]	<b>74 mm x 171 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.