TM TECHNOLOGIE

ITECH C2 305 M DALI-2 W
TM-IT.C2DLM360W


Click on the selected icon to download the file:


No: 0926 | No: 4570/2022 Valid until: 10.04.2027 | No: B_BK_60112_0422_2024 Valid until: 24.01.2030 | No: 0926 | No: 7492 | No: 0926 | No: DIT.V1.01

No: V3.0



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**escape route lighting**
Family	**ITECH**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**DALI2**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP65**
Impact protection degree	**IK06**
Appliance classes	**II**
Material	**plastic**
Colour structure	**smooth, gloss**
Installation method*	**surface, flush-mounted, suspended, ceiling, at an angle**
Luminous flux emergency	**478 lm**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Light source	**LED**
Maximum light power	**4.5 W**
Active power	**6 W**
LED lifetime	**100000 h**
Colour temperature	**5700 K**
Minimum temperature	**+ 0 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 6.4V 3.0-3.2Ah**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **H x Ø** [±2 mm]	**74 mm x 171 mm**





* Some of mounting methods are possible only with additonal accessory dedicated for that product.