

ITECH C2 305 M DALI-2 W TM-IT.C2DLM360W

Click on the selected icon to download the file:



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 7492



No: 0925



No: DIT_001





No: V2.12



DiiA Certificate

<https://www.dali-alliance.org/products/7492/itech>

Producer	TM Technologie
Category	emergency luminaires
Application	escape route lighting
Family	ITECH
Colour/Colour - RAL	white , RAL9003
Version	DALI2
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Colour structure	smooth, gloss
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	478 lm
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
Light source	LED
Maximum light power	4.5 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 3.0-3.2Ah
DALI type	A
Warranty (body, electronics, light source)	60 months
Net dimensions H x Ø [±2 mm]	74 mm x 171 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.