

ITECH S1 60 NM AT B TM-IT.S1ATN660B



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960



No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 0925




No: DIT_001




No: V2.12







| | |
|--|--|
| Producer | TM Technologie |
| Application | anti-panic lighting |
| Family | ITECH |
| Colour/Colour - RAL | black , RAL9005 |
| Version | autotest |
| Operating mode | NM |
| Duration time | 1 h |
| Protection degree | IP65 |
| Impact protection degree | IK06 |
| Appliance classes | II |
| Material | plastic |
| Installation method* | surface, flush-mounted, suspended, ceiling, at an angle |
| Luminous flux emergency | 377 lm |
| Light source | LED |
| Maximum light power | 2 W |
| Active power | 1.2 W |
| Nominal voltage AC | 210-250 V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | + 0 °C |
| Maximum temperature | +40 °C |
| Battery | LiFePO4/C (LN) 3.2V 1.5-1.6Ah |
| Warranty (body, electronics, light source) | 36 months |
| Net dimensions H x Ø [±2 mm] | 74 mm x 171 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.



| |  |  |  |  |
|-----|---|---|---|---|
| 2,5 | 6 | 14 | 6 | 14 |
| 3 | 7 | 16 | 7 | 16 |
| 4 | 8 | 18 | 8 | 18 |
| 5 | 4 | 18 | 4 | 18 |
| 6 | 3 | 17 | 3 | 17 |
| 7 | 4 | 16 | 4 | 16 |
| 8 | - | - | - | - |
| 9 | - | - | - | - |
| 10 | - | - | - | - |

$E_{min} \geq 0,5 \text{ lx}$