

ITECH S1 60 NM AT B TM-IT.S1ATN660B

Click on the selected icon to download the file:



No: 0925



No: 4570/2022
Valid until:
10.04.2027



No: 88-137960




No:
B_BK_60112_0422_2024
Valid until:
24.01.2030



No: 0925



No: 0925




No: V1



No: V2.12







Producer	TM Technologie
Application	anti-panic lighting
Family	ITECH
Colour/Colour - RAL	black , RAL9005
Version	autotest
Operating mode	NM
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK06
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, ceiling, at an angle
Luminous flux emergency	377 lm
Light source	LED
Maximum light power	2 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions H x Ø [±2 mm]	74 mm x 171 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



				
2,5	6	14	6	14
3	7	16	7	16
4	8	18	8	18
5	4	18	4	18
6	3	17	3	17
7	4	16	4	16
8	-	-	-	-
9	-	-	-	-
10	-	-	-	-

$E_{min} \geq 0,5 \text{ lx}$