TM TECHNOLOGIE

ITECH S1 60 NM ST W
TM-IT.S1STN660W

Click on the selected icon to download the file:

No: 0926 | No: 4570/2022 Valid until: 10.04.2027 | No: 88-137960 | No: B_BK_60112_0422_2024 Valid until: 24.01.2030 | No: 0926 | No: 0926 | No: V1

No: V2.12



Producer	**TM TECHNOLOGIE**
Application	**anti-panic lighting**
Family	**ITECH**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**standard**
Operating mode	**NM**
Duration time	**1 h**
Protection degree	**IP65**
Impact protection degree	**IK06**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, ceiling, at an angle**
Luminous flux emergency	**377 lm**
Light source	**LED**
Maximum light power	**2 W**
Active power	**1.2 W**
Nominal voltage AC	**210-250 V**
LED lifetime	**100000 h**
Colour temperature	**5700 K**
Minimum temperature	**+ 0 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**24 months**
Net dimensions **H x Ø** [±2 mm]	**74 mm x 171 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	6	14	6	14
3	7	16	7	16
4	8	18	8	18
5	4	18	4	18
6	3	17	3	17
7	4	16	4	16
8	-	-	-	-
9	-	-	-	-
10	-	-	-	-

Emin ≥ 0,5 lx