TM TECHNOLOGIE

# ITECH S1 60 NM ST W
# TM-IT.S1STN660W

Click on the selected icon to download the file:

No: 0926

No: 4570/2022
Valid until:
10.04.2027

No: 88-137960


No:
B_BK_60112_0422_2024
Valid until:
24.01.2030

No: 0926


No: 0926

No: DIT.V1.01


No: V3.0



| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Application | **anti-panic lighting** |
| Family | **ITECH** |
| Colour | **white** |
| Colour - RAL | **RAL9003** |
| Version | **standard** |
| Operating mode | **NM** |
| Duration time | **1 h** |
| Protection degree | **IP65** |
| Impact protection degree | **IK06** |
| Appliance classes | **II** |
| Material | **plastic** |
| Installation method* | **surface, flush-mounted, suspended, ceiling, at an angle** |
| Luminous flux emergency | **377 lm** |
| Light source | **LED** |
| Maximum light power | **2 W** |
| Active power | **1.2 W** |
| LED lifetime | **100000 h** |
| Nominal voltage AC | **210-250 V** |
| Colour temperature | **5700 K** |
| Minimum temperature | **+ 0 °C** |
| Maximum temperature | **+40 °C** |
| Battery | **LiFePO4/C (LN) 3.2V 1.5-1.6Ah** |
| Warranty (body, electronics, light source) | **24 months** |
| Net dimensions **H x Ø** [±2 mm] | **74 mm x 171 mm** |




* Some of mounting methods are possible only with additonal accessory dedicated for that product.



| h | a | b | c | d |
|---|---|---|---|---|
| 2,5 | 6 | 14 | 6 | 14 |
| 3 | 7 | 16 | 7 | 16 |
| 4 | 8 | 18 | 8 | 18 |
| 5 | 4 | 18 | 4 | 18 |
| 6 | 3 | 17 | 3 | 17 |
| 7 | 4 | 16 | 4 | 16 |
| 8 | - | - | - | - |
| 9 | - | - | - | - |
| 10 | - | - | - | - |

Emin ≥ 0,5 lx