ONTEC C C1H 303 M AT W
TM-OC.CHATM300W

Click on the selected icon to download the file:

No: 0126

No: 6232/2026
Valid until:
11.09.2031

No: 88-128463

No:
B_BK_60112_0424_2024
Valid until:
24.01.2030

No: 0126

No: 2291559.02-UAE
Valid until:
05.11.2026


No: 0126

No: DIT.V1.01


No: V3.0



Producer	**TM TECHNOLOGIE**
Application	**escape route lighting**
Family	**ONTEC C**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**autotest**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**II**
Material	**plastic**
Installation method*	**flush-mounted**
Luminous flux emergency	**353 lm**
Light source	**LED**
Maximum light power	**3 W**
Active power	**8.6 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 6.4V 3.0-3.2Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **H x Ø** [±2 mm]	**14 mm x 90 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	9,5	21	-	-
3	10,5	24	-	-
4	12,5	29,5	-	-
5	13,5	34	-	-
6	11,5	36	-	-
7	6,5	34	-	-
8	4,5	30	-	-
9	4	25	-	-
10	4	20	-	-

Emin ≥ 1 lx