
# ONTEC E E1E 01 CB W
# TM-OE.EECB0000W

Click on the selected icon to download the file:

No: 0226 | No: 6233/2026 Valid until: 10.10.2026 | No: 88-141776 Valid until: 31.12.2027 | No: B_BK_60112_0425_2024 Valid until: 24.01.2030 | No: 0226 | No: 2314475.01-UAE Valid until: 19.10.2028 | No: 0226 | No: V3.0



| | |
|---|---|
| Producer | **TM TECHNOLOGIE** |
| Category | **emergency luminaires** |
| Application | **evacuation route direction** |
| Family | **ONTEC E** |
| Colour | **white** |
| Colour - RAL | **RAL9003** |
| Colour structure | **matte , satin, smooth** |
| Version | **CB - central battery** |
| Operating mode | **CB** |
| Protection degree | **IP20** |
| Impact protection degree | **IK05** |
| Appliance classes | **II** |
| Material | **plastic** |
| Installation method* | **surface, flush-mounted, wall** |
| Adapted to use a pictogram | **yes** |
| Pictogram included | **yes** |
| Pictogram dimensions | **265x139 mm** |
| Evacuation sign dimensions | **250x125 mm** |
| Pictogram type | **foil** |
| Graphic number | **K3** |
| Luminous flux | **>150 cd/m²** |
| Visibility | **25 m** |
| Colour temperature | **5700 K** |
| Nominal voltage AC | **210-250 V** |
| Nominal voltage DC | **186-254 V** |
| Light source | **LED** |
| Maximum light power | **1.5 W** |
| Active power | **2.4 W** |
| LED lifetime | **50000 h** |
| Minimum temperature | **-15 °C** |
| Maximum temperature | **+55 °C** |
| Warranty (body, electronics, light source) | **60 months** |
| Net dimensions **L x W x H** [±2 mm] | **277 mm x 33 mm x 153 mm** |




* Some of mounting methods are possible only with additonal accessory dedicated for that product.