

# ONTEC E E1P 01 CB I TM-OE.EPCB0000I

Click on the selected icon to download the file:



No: 0225



No: 4408/2021  
Valid until:  
09.10.2026



No: B\_BK\_60112\_0425\_2024  
Valid until:  
24.01.2030



No: 0225



No: 0225



No: V1.12



|                            |                                     |
|----------------------------|-------------------------------------|
| Producer                   | <b>TM TECHNOLOGIE</b>               |
| Category                   | <b>emergency luminaires</b>         |
| Application                | <b>evacuation route direction</b>   |
| Family                     | <b>ONTEC E</b>                      |
| Colour/Colour - RAL        | <b>blue , RAL5015</b>               |
| Colour structure           | <b>matte , satin, smooth</b>        |
| Version                    | <b>CB1 - central battery</b>        |
| Operating mode             | <b>CB</b>                           |
| Protection degree          | <b>IP20</b>                         |
| Impact protection degree   | <b>IK05</b>                         |
| Appliance classes          | <b>II</b>                           |
| Material                   | <b>plastic</b>                      |
| Installation method*       | <b>surface, flush-mounted, wall</b> |
| Adapted to use a pictogram | <b>yes</b>                          |
| Pictogram included         | <b>yes</b>                          |
| Pictogram dimensions       | <b>265x139 mm</b>                   |
| Evacuation sign dimensions | <b>250x125 mm</b>                   |
| Pictogram type             | <b>foil</b>                         |
| Graphic number             | <b>K3</b>                           |
| Luminous flux              | <b>&gt;300 cd/m<sup>2</sup></b>     |
| Visibility                 | <b>25 m</b>                         |
| Colour temperature         | <b>5700 K</b>                       |
| Nominal voltage AC         | <b>210-250 V</b>                    |
| Nominal voltage DC         | <b>186-254 V</b>                    |
| Light source               | <b>LED</b>                          |
| Maximum light power        | <b>1 W</b>                          |
| LED lifetime               | <b>50000 h</b>                      |
| Minimum temperature        | <b>-15 °C</b>                       |
| Maximum temperature        | <b>+55 °C</b>                       |

|                                            |                                |
|--------------------------------------------|--------------------------------|
| Warranty (body, electronics, light source) | <b>60 months</b>               |
| Net dimensions <b>L x W x H</b> [±2 mm]    | <b>277 mm x 33 mm x 153 mm</b> |

