

ONTEC E E1P 01 CB I
TM-OE.EPCB0000I

Click on the selected icon to download the file:

No: 0226 | No: 6233/2026 Valid until: 10.10.2026 | No: B_BK_60112_0425_2024 Valid until: 24.01.2030 | No: 0226 | No: 0226 | No: V3.0



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**ONTEC E**
Colour	**blue**
Colour - RAL	**RAL5015**
Colour structure	**matte , satin, smooth**
Version	**CB1 - central battery**
Operating mode	**CB**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, wall**
Adapted to use a pictogram	**yes**
Pictogram included	**yes**
Pictogram dimensions	**265x139 mm**
Evacuation sign dimensions	**250x125 mm**
Pictogram type	**foil**
Graphic number	**K3**
Luminous flux	**>300 cd/m²**
Visibility	**25 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**186-254 V**
Light source	**LED**
Maximum light power	**1 W**
Active power	**2.7 W**
LED lifetime	**50000 h**
Minimum temperature	**-15 °C**
Maximum temperature	**+55 °C**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**277 mm x 33 mm x 153 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.