

# ONTEC E E1P 01 CB L TM-OE.EPCB0000L

Click on the selected icon to download the file:



No: 0225



No: 4408/2021  
Valid until:  
09.10.2026



No: B\_BK\_60112\_0425\_2024  
Valid until:  
24.01.2030



No: 0225



No: 0225




No: V1.12



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>evacuation route direction</b>
Family	<b>ONTEC E</b>
Colour/Colour - RAL	<b>yellow , RAL1016</b>
Colour structure	<b>matte , satin, smooth</b>
Version	<b>CB1 - central battery</b>
Operating mode	<b>CB</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK05</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Installation method*	<b>surface, flush-mounted, wall</b>
Adapted to use a pictogram	<b>yes</b>
Pictogram included	<b>yes</b>
Pictogram dimensions	<b>265x139 mm</b>
Evacuation sign dimensions	<b>250x125 mm</b>
Pictogram type	<b>foil</b>
Graphic number	<b>K3</b>
Luminous flux	<b>&gt;300 cd/m<sup>2</sup></b>
Visibility	<b>25 m</b>
Colour temperature	<b>5700 K</b>
Nominal voltage AC	<b>210-250 V</b>
Nominal voltage DC	<b>186-254 V</b>
Light source	<b>LED</b>
Maximum light power	<b>1 W</b>
LED lifetime	<b>50000 h</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+55 °C</b>

Warranty (body, electronics, light source) **60 months**  
Net dimensions **L x W x H [±2 mm]** **277 mm x 33 mm x 153 mm**



\* Some of mounting methods are possible only with additional accessory dedicated for that product.