

ONTEC E E1P 301 M DALI W TM-OE.EPDAM300W



No: 0225



No: 4408/2021
Valid until:
09.10.2026



No:
B_BK_60112_0425_2024
Valid until:
24.01.2030



No: 0225



No: 3333



No: 0225



No: DIT_001



No: V1.12



DiiA Certificate

<https://www.dali-alliance.org/products/3333/vip-r>

Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC E
Colour/Colour - RAL	white , RAL9003
Colour structure	matte , satin, smooth
Version	DALI
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, wall
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	265x139 mm
Evacuation sign dimensions	250x125 mm
Pictogram type	foil
Graphic number	K3
Luminous flux	>300 cd/m²
Visibility	25 m
Colour temperature	5700 K
Nominal voltage AC	210-250 V
Light source	LED
Maximum light power	1 W
LED lifetime	50000 h
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C 6.4V 1.5Ah
DALI type	A
Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	277 mm x 33 mm x 153 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.