ONTEC G E1E 180 M AT C
TM-OG.EEATM800C

Click on the selected icon to download the file:

No: 0326

No: 6227/2026
Valid until:
05.09.2031

No: 88-128652

No:
B_BK_60112_0425_2024
Valid until:
24.01.2030

No: 0326

No: 2291559.02-UAE
Valid until:
05.11.2026

No: 0326

No: DIT.V1.01

No: V3.0



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**evacuation route direction**
Family	**ONTEC G**
Colour	**red**
Colour - RAL	**RAL3020**
Colour structure	**matte , satin, smooth**
Version	**autotest**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK05**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, suspended, wall, ceiling**
Adapted to use a pictogram	**yes**
Pictogram included	**yes**
Pictogram dimensions	**125x125 mm**
Evacuation sign dimensions	**250x125 mm**
Pictogram type	**foil**
Graphic number	**K6**
Pictogram logo	**TM TECHNOLOGIE**
Luminous flux	**>350 cd/m²**
Visibility	**25 m**
Colour temperature	**5700 K**
Nominal voltage AC	**210-250 V**
Nominal voltage DC	**- V**
Light source	**LED**
Maximum light power	**0.9 W**
Active power	**3 W**
LED lifetime	**50000 h**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **L x W x H** [±2 mm]	**251 mm x 29 mm x 198 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.