

ONTEC G E1P 301 M DALI-2 W TM-OG.EPDLM300W

Click on the selected icon to download the file:



No: 03A25



No: 4420/2021
Valid until:
05.09.2026



No: B_BK_60112_0425_2024
Valid until:
24.01.2030




No: 03A25



No: 7090



No: 03A25



No: DIT_001




No: V1.19



DiiA Certificate

<https://www.dali-alliance.org/products/7090/vip-r>

| | |
|--|---|
| Producer | TM Technologie |
| Category | emergency luminaires |
| Application | evacuation route direction |
| Family | ONTEC G |
| Colour/Colour - RAL | white , RAL9003 |
| Colour structure | matte , satin, smooth |
| Version | DALI2 |
| Operating mode | M |
| Duration time | 3 h |
| Protection degree | IP20 |
| Impact protection degree | IK05 |
| Appliance classes | II |
| Material | plastic |
| Installation method* | surface, flush-mounted, suspended, wall, ceiling |
| Adapted to use a pictogram | yes |
| Pictogram included | yes |
| Pictogram dimensions | 125x125 mm |
| Evacuation sign dimensions | 250x125 mm |
| Pictogram type | foil |
| Graphic number | K6 |
| Pictogram logo | TM Technologie |
| Luminous flux | >350 cd/m² |
| Visibility | 25 m |
| Colour temperature | 5700 K |
| Nominal voltage AC | 210-250 V |
| Nominal voltage DC | - V |
| Light source | LED |
| Maximum light power | 1.8 W |
| LED lifetime | 50000 h |
| Minimum temperature | +10 °C |
| Maximum temperature | +35 °C |
| Battery | LiFePO4/C (LN) 6.4V 1.5-1.6Ah |
| DALI type | A |
| Warranty (body, electronics, light source) | 60 months |
| Net dimensions L x W x H [±2 mm] | 251 mm x 29 mm x 198 mm |



* Some of mounting methods are possible only with additional accessory dedicated for that product.