

ONTEC R C1 302 M AT B

TM-OR.C1ATM300B

Click on the selected icon to download the file:



No: 0425



No: 4410/2021
Valid until:
04.09.2026



No: 88-128814



No:
B_BK_60112_0424_2024
Valid until:
24.01.2030



No: 0425



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 0425



No: V1



No: V3.0



| | |
|--|---|
| Producer | TM TECHNOLOGIE |
| Application | escape route lighting |
| Family | ONTEC R |
| Colour/Colour - RAL | black , RAL9005 |
| Version | autotest |
| Operating mode | M |
| Duration time | 3 h |
| Protection degree | IP20 |
| Impact protection degree | IK03 |
| Appliance classes | II |
| Material | plastic |
| Installation method* | surface, flush-mounted, wall, ceiling, at an angle |
| Luminous flux emergency | 246 lm |
| Light source | LED |
| Maximum light power | 2 W |
| Active power | 7.2 W |
| Nominal voltage AC | 210-250 V |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | +10 °C |
| Maximum temperature | +35 °C |
| Battery | LiFePO4/C (LN) 6.4V 1.5-1.6Ah |
| Warranty (body, electronics, light source) | 36 months |
| Net dimensions L x W x H [±2 mm] | 130 mm x 31 mm x 130 mm |





| | | | | |
|-----|-----|----|---|---|
| 2,5 | 8,5 | 19 | - | - |
| 3 | 9,5 | 22 | - | - |
| 4 | 11 | 26 | - | - |
| 5 | 12 | 30 | - | - |
| 6 | 5,5 | 30 | - | - |
| 7 | 4,5 | 20 | - | - |
| 8 | 4 | 18 | - | - |
| 9 | - | - | - | - |
| 10 | - | - | - | - |

$E_{min} \geq 1 \text{ lx}$