ONTEC R C1 302 M AT W
TM-OR.C1ATM300W

Click on the selected icon to download the file:

No: 0426

No: 6228/2026
Valid until:
04.09.2031

No: 88-128814

No:
B_BK_60112_0424_2024
Valid until:
24.01.2030

No: 0426

No: 2291559.02-UAE
Valid until:
05.11.2026

No: 0426

No: DIT.V1.01

No: V3.0



Producer	**TM TECHNOLOGIE**
Application	**escape route lighting**
Family	**ONTEC R**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**autotest**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**II**
Material	**plastic**
Installation method*	**surface, flush-mounted, wall, ceiling, at an angle**
Luminous flux emergency	**246 lm**
Light source	**LED**
Maximum light power	**2 W**
Active power	**7.2 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 6.4V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**36 months**
Net dimensions **L x W x H** [±2 mm]	**130 mm x 31 mm x 130 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	8,5	19	-	-
3	9,5	22	-	-
4	11	26	-	-
5	12	30	-	-
6	5,5	30	-	-
7	4,5	20	-	-
8	4	18	-	-
9	-	-	-	-
10	-	-	-	-

Emin ≥ 1 lx