

ONTEC S C1 302 M AT W TM-OS.C1ATM360W

Click on the selected icon to download the file:



No: 1025



No: 4662/2022
Valid until:
02.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1025



No: 2291559.02-
UAE
Valid until:
05.11.2026



No: 1025




No: V1



No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	M
Duration time	3 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	225 lm
Light source	LED
Maximum light power	2 W
Active power	6.5 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+ 0 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	7,5	17	-	-
3	8	19,5	-	-
4	8	23	-	-
5	7	25	-	-
6	4,5	24	-	-
7	4	21	-	-
8	3,5	17	-	-
9	5	10	-	-
10	/	/	-	-

$E_{min} \geq 1 \text{ lx}$