

ONTEC S C1 CB W TM-OS.C1CB0060W

Click on the selected icon to download the file:



No: 1025



No: 4662/2022
Valid until:
02.06.2027



No: 88-142217
Valid until:
30.07.2029



No:
B_BK_60112_0426_2024
Valid until:
24.01.2030



No: 1025



No: 2291559.01-
UAE
Valid until:
28.10.2026



No: 1025









No: V3.0



Producer	TM Technologie
Application	escape route lighting
Family	ONTEC S
Colour/Colour - RAL	white , RAL9003
Version	CB - central battery
Operating mode	CB
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	282 lm
Light source	LED
Maximum light power	2 W
Active power	4.5 W
Nominal voltage AC	210-250 V
Nominal voltage DC	186-254 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-15 °C
Maximum temperature	+55 °C

Warranty (body, electronics, light source)	60 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm





2,5	8	18	-	-
3	8,5	20,5	-	-
4	9,5	25	-	-
5	9	27,5	-	-
6	6,5	28	-	-
7	5	26	-	-
8	4,5	23	-	-
9	4	20	-	-
10	4	15	-	-

$E_{min} \geq 1 \text{ lx}$