

# ONTEC S C1 302 M DALI W COLD TM-OS.C1DAM36CW

Click on the selected icon to download the file:



No: 1025



No: 4662/2022  
Valid until:  
02.06.2027



No: 1025  
B\_BK\_60112\_0426\_2024  
Valid until:  
24.01.2030



No: 1025



No: 4909



No: 1025



No: DIT\_001




No: V3.0








DiiA Certificate

<https://www.dali-alliance.org/products/4909/vip-rs>

Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>escape route lighting</b>
Family	<b>ONTEC S</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>DALI</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP65</b>
Impact protection degree	<b>IK08</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Colour structure	<b>smooth, gloss</b>
Installation method*	<b>surface, flush-mounted, suspended, wall, ceiling, at an angle</b>
Luminous flux emergency	<b>225 lm</b>
Nominal voltage AC	<b>210-250 V</b>
Light source	<b>LED</b>
Maximum light power	<b>2 W</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>-15 °C</b>
Maximum temperature	<b>+40 °C</b>
Battery	<b>LiFePO4/C 6.4V 3.0Ah</b>
DALI type	<b>A</b>
Warranty (body, electronics, light source)	<b>60 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>272 mm x 40 mm x 144 mm</b>



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	7,5	17	-	-
3	8	19,5	-	-
4	8	23	-	-
5	7	25	-	-
6	4,5	24	-	-
7	4	21	-	-
8	3,5	17	-	-
9	5	10	-	-
10	/	/	-	-

$E_{min} \geq 1 \text{ lx}$