
ONTEC S C1 302 M DALI W COLD
TM-OS.C1DAM36CW

Click on the selected icon to download the file:


No: 1026 | No: 4662/2022 Valid until: 02.06.2027 | No: B_BK_60112_0426_2024 Valid until: 24.01.2030 | No: 1026 | No: 4909 | No: 1026 | No: DIT.V1.01 | No: V3.1



Producer	**TM TECHNOLOGIE**
Category	**emergency luminaires**
Application	**escape route lighting**
Family	**ONTEC S**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**DALI**
Operating mode	**M**
Duration time	**3 h**
Protection degree	**IP65**
Impact protection degree	**IK08**
Appliance classes	**II**
Material	**plastic**
Colour structure	**smooth, gloss**
Installation method*	**surface, flush-mounted, suspended, wall, ceiling, at an angle**
Luminous flux emergency	**225 lm**
Nominal voltage AC	**210-250 V**
Light source	**LED**
Maximum light power	**2 W**
Active power	**6.5 W**
LED lifetime	**50000 h**
Colour temperature	**5700 K**
Minimum temperature	**-15 °C**
Maximum temperature	**+40 °C**
Battery	**LiFePO4/C 6.4V 3.0Ah**
DALI type	**A**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**272 mm x 40 mm x 144 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	7,5	17	-	-
3	8	19,5	-	-
4	8	23	-	-
5	7	25	-	-
6	4,5	24	-	-
7	4	21	-	-
8	3,5	17	-	-
9	5	10	-	-
10	/	/	-	-

Emin ≥ 1 lx