

ONTEC S M5 105 M ST B COLD TM-OS.M5STM16CB

Click on the selected icon to download the file:



No: 1025



No: 4662/2022
Valid until:
01.06.2027



No: 88-139797



No:
B_BK_60112_0426_2024
Valid until:
23.01.2030



No: 1025



No: 2291559.02-
UAE
Valid until:
04.11.2026




No: 1025



No: V3.0



Producer	TM Technologie
Application	anti-panic lighting
Family	ONTEC S
Colour/Colour - RAL	black , RAL9005
Version	standard
Operating mode	M
Duration time	1 h
Protection degree	IP65
Impact protection degree	IK08
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling, at an angle
Luminous flux emergency	576 lm
Light source	LED
Maximum light power	4.5 W
Active power	6.8 W
Nominal voltage AC	210-250 V
Nominal voltage DC	- V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	-15 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C 6.4V 3.0Ah
Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	272 mm x 40 mm x 144 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.