

PRIMO P M2 180 NM AT W TM-P0.M2.AT04W



No: 1725



No: 4329/2021
Valid until:
19.05.2026



No:
B_BK_60112_0427_2024
Valid until:
24.01.2030



No: 1725



No: DC-UAE-
0180
Valid until:
19.05.2026



No: 1725





No: DIT_001



No: V1.2



Producer	TM Technologie
Application	anti-panic lighting
Family	PRIMO P
Colour/Colour - RAL	white , RAL9003
Version	autotest
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	I
Material	steel
Installation method*	flush-mounted, ceiling
Luminous flux emergency	651 lm
Light source	LED
Maximum light power	5.1 W
Active power	3.6 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+5 °C
Maximum temperature	+40 °C
Battery	LiFePO4/C (LN) 6.4V 4.5-4.8Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	357 mm x 90 mm x 88 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.