

# PRIMO C C1 60 NM DATA2 B TM-PC.C1BDN600B

Click on the selected icon to download the file:



No: 0525



No: 4672/2022  
Valid until:  
13.06.2027



No: 88-128507



No:  
B\_BK\_60112\_0428\_2024  
Valid until:  
24.01.2030



No: 0525



No: DC-UAE-  
0214  
Valid until:  
13.06.2027



No: 0525



No: V1



No: V1.5



|  |                                      |
|--|--------------------------------------|
| Producer                                   | <b>TM Technologie</b>                |
| Application                                | <b>escape route lighting</b>         |
| Family                                     | <b>PRIMO C</b>                       |
| Colour/Colour - RAL                        | <b>black , RAL9005</b>               |
| Version                                    | <b>DATA2</b>                         |
| Operating mode                             | <b>NM</b>                            |
| Duration time                              | <b>1 h</b>                           |
| Protection degree                          | <b>IP20</b>                          |
| Impact protection degree                   | <b>IK03</b>                          |
| Appliance classes                          | <b>I</b>                             |
| Material                                   | <b>steel</b>                         |
| Installation method*                       | <b>flush-mounted</b>                 |
| Luminous flux                              | <b>- cd/m<sup>2</sup></b>            |
| Luminous flux emergency                    | <b>279 lm</b>                        |
| Light source                               | <b>LED</b>                           |
| Maximum light power                        | <b>3 W</b>                           |
| Active power                               | <b>1.2 W</b>                         |
| Nominal voltage AC                         | <b>210-250 V</b>                     |
| LED lifetime                               | <b>50000 h</b>                       |
| Colour temperature                         | <b>5700 K</b>                        |
| Minimum temperature                        | <b>+10 °C</b>                        |
| Maximum temperature                        | <b>+35 °C</b>                        |
| Battery                                    | <b>LiFePO4/C (LN) 3.2V 1.5-1.6Ah</b> |
| Warranty (body, electronics, light source) | <b>60 months</b>                     |
| Net dimensions <b>H x Ø</b> [±2 mm]        | <b>13 mm x 90 mm</b>                 |



\* Some of mounting methods are possible only with additional accessory dedicated for that product.



|     |      |    |   |   |
|-----|------|----|---|---|
| 2,5 | 9    | 20 | - | - |
| 3   | 10   | 23 | - | - |
| 4   | 11,5 | 28 | - | - |
| 5   | 9,5  | 31 | - | - |
| 6   | 5    | 30 | - | - |
| 7   | 4    | 28 | - | - |
| 8   | 4    | 21 | - | - |
| 9   | 3    | 16 | - | - |
| 10  | 3,5  | 13 | - | - |

$E_{min} \geq 1 \text{ lx}$