

PRIMO C C1 60 NM DATA2 M TM-PC.C1BDN600M

Click on the selected icon to download the file:



No: 0525



No: 4672/2022
Valid until:
13.06.2027



No: 88-128507



No:
B_BK_60112_0428_2024
Valid until:
24.01.2030



No: 0525



No: DC-UAE-
0214
Valid until:
13.06.2027



No: 0525




No: DIT_001



No: V1.5



Producer	TM Technologie
Application	escape route lighting
Family	PRIMO C
Version	DATA2
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	I
Material	stainless steel
Installation method*	flush-mounted
Luminous flux	- cd/m²
Luminous flux emergency	279 lm
Light source	LED
Maximum light power	3 W
Active power	1.2 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 3.2V 1.5-1.6Ah
Warranty (body, electronics, light source)	60 months
Net dimensions H x Ø [±2 mm]	13 mm x 90 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	9	20	-	-
3	10	23	-	-
4	11,5	28	-	-
5	9,5	31	-	-
6	5	30	-	-
7	4	28	-	-
8	4	21	-	-
9	3	16	-	-
10	3,5	13	-	-

$E_{min} \geq 1 \text{ lx}$