

PRIMO C M2 302 M DATA2 W TM-PC.M2BDM300W

Click on the selected icon to download the file:



No: 0525



No: 4672/2022
Valid until:
13.06.2027



No: 88-128507



No:
B_BK_60112_0428_2024
Valid until:
24.01.2030



No: 0525



No: DC-UAE-
0214
Valid until:
13.06.2027



No: 0525



No: V1




No: V1.5



Producer	TM Technologie
Application	anti-panic lighting
Family	PRIMO C
Colour/Colour - RAL	white , RAL9003
Version	DATA2
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	I
Material	steel
Installation method*	flush-mounted
Luminous flux	- cd/m²
Luminous flux emergency	224 lm
Light source	LED
Maximum light power	3 W
Active power	7 W
Nominal voltage AC	210-250 V
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	+10 °C
Maximum temperature	+35 °C
Battery	LiFePO4/C (LN) 6.4V 1.5-1.6Ah
Warranty (body, electronics, light source)	60 months
Net dimensions H x Ø [±2 mm]	13 mm x 90 mm



* Some of mounting methods are possible only with additional accessory dedicated for that product.



2,5	3,5	7,5	3,5	7,5
3	3,5	8,5	3,5	8,5
4	4	10,5	4	10,5
5	5	12	5	12
6	5	14	5	14
7	5	15	5	15
8	4,5	16	4,5	16
9	3	17	3	17
10	4	16	4	16

$E_{min} \geq 0,5 \text{ lx}$