PRIMO D C1 60 NM DATA2 W
TM-PD.C1BDN600W


Click on the selected icon to download the file:

No: 0526 | No: 4672/2022 Valid until: 13.06.2027 | No: 88-128507 | No: B_BK_60112_0428_2024 Valid until: 24.01.2030 | No: 0526 | No: DC-UAE-0214 Valid until: 13.06.2027 | No: 0526


No: DIT.V1.01 | No: V3.1



Producer	**TM TECHNOLOGIE**
Application	**escape route lighting**
Family	**PRIMO D**
Colour	**white**
Colour - RAL	**RAL9003**
Version	**DATA2**
Operating mode	**NM**
Duration time	**1 h**
Protection degree	**IP20**
Impact protection degree	**IK03**
Appliance classes	**I**
Material	**steel**
Installation method*	**flush-mounted, ceiling**
Luminous flux	**- cd/m²**
Luminous flux emergency	**279 lm**
Light source	**LED**
Maximum light power	**3 W**
Active power	**1.2 W**
LED lifetime	**50000 h**
Nominal voltage AC	**210-250 V**
Colour temperature	**5700 K**
Minimum temperature	**+10 °C**
Maximum temperature	**+35 °C**
Battery	**LiFePO4/C (LN) 3.2V 1.5-1.6Ah**
Warranty (body, electronics, light source)	**60 months**
Net dimensions **L x W x H** [±2 mm]	**90 mm x 90 mm x 13 mm**



* Some of mounting methods are possible only with additonal accessory dedicated for that product.



h	a	b	c	d
2,5	9	20	-	-
3	10	23	-	-
4	11,5	28	-	-
5	9,5	31	-	-
6	5	30	-	-
7	4	28	-	-
8	4	21	-	-
9	3	16	-	-
10	3,5	13	-	-

Emin ≥ 1 lx